


Pro H610T D4-CSM

[Visión general](#)
[Especificaciones técnicas](#)
[Revisar](#)
[Apoyo](#)


UPC

Intel® Socket LGA1700 para procesadores Intel® Core™, Pentium® Gold y Celeron® de 12.ª generación*

Compatible con la tecnología Intel® Turbo Boost 2.0 y la tecnología Intel® Turbo Boost Max 3.0**

*CPU solo admite hasta 65W

*Consulte www.asus.com para ver la lista de soporte de CPU.

**La compatibilidad con Intel® Turbo Boost Max Technology 3.0 depende de los tipos de CPU.

conjunto de chips

Conjunto de chips Intel® H610

Memoria

2 SO-DIMM, máx. 64 GB, DDR4 3200/2933/2800/2666/2400/2133 MHz sin ECC, memoria sin búfer*

Arquitectura de memoria de doble canal

Admite el perfil de memoria Intel® Extreme (XMP)

*La compatibilidad con la velocidad de datos de la memoria real depende de los tipos de CPU y los módulos DRAM; para obtener más información, consulte www.asus.com para la QVL de memoria (Listas de proveedores calificados).

Gráficos

1 puerto de pantalla**

1 x puerto HDMI® ***

1 connector LVDS

*Graphics specifications may vary between CPU types.

** Supports max. 4K@60Hz as specified in DisplayPort 1.4.

*** Supports 4K@60Hz as specified in HDMI 2.1.

Storage

Total supports 1 x M.2 slot and 2 x SATA 6Gb/s ports

Intel® 12th Gen Processors

- 1 x M.2 slot (Key M), type 2260/2280 (supports PCIe 4.0 x4 & SATA modes)

Intel® H610 Chipset

- 2 x SATA 6.0 Gb/s ports

Ethernet

1 x Realtek 1Gb Ethernet

ASUS LANGuard

USB

Rear USB (Total 4 ports)

2 x USB 3.2 Gen 2 ports (2 x Type-A)

2 x USB 2.0 ports

Front USB (Total 7 ports)

1 x USB 3.2 Gen 1 header supports additional 2 USB 3.2 Gen 1 ports

2 x USB 2.0 headers support additional 4 USB 2.0 ports

1 x USB 2.0 header supports additional 1 USB 2.0 port

Audio

Realtek 7.1 Surround Sound High Definition Audio CODEC*

- Supports: Jack-detection, Front Panel Jack-retasking

- Supports up to 24-Bit/192 kHz playback "

* A chassis with an HD audio module in the front panel is required to support 7.1 Surround Sound audio output.

Back Panel I/O Ports

2 x USB 3.2 Gen 2 ports

2 x USB 2.0 ports

1 x DisplayPort

1 x HDMI® port

1 x Realtek 1Gb Ethernet port

2 x Audio jacks

1 x DC Power Connector (Support 19V)

Internal I/O Connectors

Fan and Cooling related

1 x 4-pin CPU Fan header

1 x 4-pin Chassis Fan header

Power related

1 x 2-pin +19V Power connector

1 x SATA power connector

Storage related

1 x M.2 slot (Key M)

2 x SATA 6Gb/s ports

USB

1 x USB 3.2 Gen 1 header supports additional 2 USB 3.2 Gen 1 ports

2 x USB 2.0 header supports additional 4 USB 2.0 ports

1 x USB 2.0 header supports additional 1 USB 2.0 ports

AIO System related

1 x 2-pin internal DC power connector

1 x Stereo speaker connector

1 x DMIC header

Flat panel display related

1 x Backlight inverter voltage selection header

1 x FPD brightness header

1 x Panel voltage selection header

1 x Panel off header

Miscellaneous

1 x Clear CMOS header

1 x Chassis Intrude header

1 x COM Port header

1 x COM debug header

	1 x Front Panel Audio header (AAPF) 1 x LVDS connector 1 x M.2 slot (Key E) 1 x Speaker header 1 x SPI TPM header (14-1pin) 1 x 10-1 pin System Panel header
BIOS	128 Mb Flash ROM, UEFI AMI BIOS
Manageability	WOL by PME, PXE
Accessories	Cables 2 x SATA 6Gb/s cables 1 x SATA power cable Miscellaneous 2 x I/O Shields Installation Media 1 x Support DVD Documentation 1 x ACC Express Activation Key Card 1 x User guide
Operating System	Windows® 11 64-bit, Windows® 10 64-bit
Form Factor	Thin Mini-ITX Form Factor 6.7" x 6.7" (17.0cm x 17.0cm)