

## DVR



Provision-ISR DVRs feature the advanced H.264-H265 video compression format for maximum video quality alongside minimum storage volume. Their Dynamic Hybrid function allows installers to decide how the analog channels will work according to the installation needs, making this installation totally dynamic.



# SH-8100A5N-2L(MM)

## 8CH "4 In 1" + 2CH IP Dynamic Hybrid DVR

Provision-ISR SH-8100A5N-2L(MM) is a high-quality dynamic hybrid digital video recorder obtainable in an elegant mini metal case. This technology allows users to add advanced IP cameras alongside analog ones and enjoy high-quality images and other advanced features available on IP cameras only. The recorder supports Provision-ISR Standard Video Analytics (Pixel Based).



## MAIN FEATURES

- SH-8100A5N-2L(MM) Video Input: 8CH Standard BNC + 2CH IP
- Video Output:
- HDMI - FHD
- VGA Recording:
- HD Analog: 2MP lite / 1MP: Up to 12/15FPS Per Channel
- CVBS: 960H: Up to 25/30FPS Per Channel
- IP: 5MP and lower: 25/30FPS Per Channel Playback:
- Local: 8Ch Simultaneously
- Remote: 4Ch Simultaneously Audio:
- Input: 1CH + IPC Inputs

- Output: 1CH + IPC Outputs Alarm:
- Input: IP Cameras only
- Output: IP Cameras only Storage:
- 1 x SATA (Up to 6TB each) Network:
- 1 x RJ-45: 10/100Mbps PTZ Support:
- CoC / IP over Network Power Supply:
- DC12V/2A Analytics: AI by IPC:
- DDA1 Analytics Supported by the camera Based on FW Version: v1.3.8 Features subject to firmware version changes



<https://provision-isr.com>

## SPECIFICATIONS

NDAA Compliant	
NDAA Compliant	Yes
General	
Technology	Hybrid DVR
Recording Modes	Schedule, Manual, Motion, Sensor, Analytics, POS
Format	"All in 1" Hybrid (AHD / CVI / TVI / CVBS + IP)
Video Input	
Video Input (Max Analog)	8CH Standard BNC + 2CH IP (Over Network)
Video Input (Max IP)	10CH IP (Over Network) + 0CH Standard BNC
3K Input Support	No
Video Output	
Video Output	HDMI(1920x1080), VGA (1280x1024, 1024x768)
Dual Output	Mirrored
Audio	
Audio-In	1CH RCA (2.0 Vp-p, 1 k $\Omega$ ) (+IP Cameras)
Audio-Out	1CH RCA (2.0 Vp-p, 1 k $\Omega$ ) (+IP Cameras)
Audio Over Coax	No
Two Way Audio	Yes
Audio Compression	G.711u
Events and Analytics	
SMD Support	No
DDA Analytics (On Analog Channels)	No
Pixel Based Analytics	Yes
Main Resolution and FPS	

<b>IP Main Stream</b>	5MP and lower: 25/30FPS Per Channel
<b>AHD</b>	AHD 2MP lite / 1MP: Up to 12/15FPS Per Channel
<b>TVI</b>	2MP lite / 1MP: Up to 12/15FPS Per Channel
<b>CVI</b>	2MP lite / 1MP: Up to 12/15FPS Per Channel
<b>CVBS Main Stream</b>	CVBS: 960H: Up to 25/30FPS Per Channel
<b>Master Stream Over Network</b>	4Ch

Network (Substream) Resolution and FPS	
<b>HD Analog</b>	1-25/30FPS@D1 Per Channel (FPS Restricted to Master Stream FPS)
<b>IP Sub Stream</b>	1-25/30FPS@D1 Per Channel
<b>CVBS Sub Stream</b>	1-25/30FPS@D1 Per Channel
<b>Substreams over Network</b>	50 (Outgoing bandwidth limit applies)

Remote view	
<b>Max Channel View</b>	50Ch (Limited to Outgoing Bandwidth Capacity)

Video Compression	
<b>Video Compression</b>	H.265 (HEVC) / H.264

Record	
<b>Recording Mode</b>	Main Stream only

Remote Applications	
<b>User Access</b>	5 Users Online with Professional Authority Management
<b>Mobile App</b>	Provision Cam2 for iOS/Android
<b>PC/Mac Software</b>	Ossia VMS Standard / Enterprise
<b>Plug-in free Web-Browser</b>	Chrome, FireFox, Safari, Edge, Opera. (All Limited to 4Ch Live View / Playback)
<b>Plug-in based Web-Browser</b>	Internet Explorer

Bandwidth	
Incoming	16Mbps
Outgoing	60Mbps
Playback	
Local Playback Channels	8Ch
Remote Playback Channels	4Ch
Search Modes	Time-Slice, Time, Event, File Management, Smart Search
Backup	
USB	2 USB 2.0 Port
Backup Format	AVI/DAT
Alarm	
Alarm-in	IP Cameras only
Alarm-out	IP Cameras only
Alarm Box Support	No
Storage	
HDD Max Capacity	6TB
Total HDD Max Capacity	6TB
Number of HDD	1
E-Sata	No
PTZ	
Connection	CoC / IP over Network
Supported Protocols	Pelco D, Pelco P, Samsung, Visca, ONVIF, CoC
Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus

# SH-8100A5N-2L(MM)



Network	
Ethernet	100 Mbps (RJ-45)
Protocols	TCP/IP, DHCP, DDNS, NTP, SMTP, RTSP, HTTPS, FTP, SNMP, P2P, POS
ONVIF	Yes (For IP Channels)
Others	
Dimensions	W255xD220xH43mm
Power Supply	DC12V/2A
Operation Temperature	0°C ~50°C