



TAPO L930-10

Color	RGBW LED
Energy Consumption	24 W
Voltage	100-240 V AC, 50/60 Hz
Color de Temperatura	2,500-6,500 K
Índice de Reproducción Cromática	>80
Warm-up Time	<1s
Nominal Luminous Flux	2000 lm (200 lm/m)
Regulable	1%-100% (via app and cloud only)
Lifetime	25000 H
Colour Changing	Yes (via app and cloud only)
Standby Power	0.4 W
Number of LED Beads	300 RGB LEDs +300 White LEDs
GENERAL	
Contenidos del Paquete	LED Light Strip (2 *5 m / 2*16.4 ft) Power Adapter Controller 3M Adhesive for Controller Quick Start Guide
Product Dimensions	5000*10*3.0 mm (Each)
Certification	CE, FCC, IC, JRF, VCCI, RCM, NCC, BSMI, RoHS
Temperatura de Funcionamiento	-15 °C~40 °C (5 °F ~ 104°F)
Humedad de funcionamiento	10%~90% RH, Non-condensing
Weight	806~891 g
COMUNICACIÓN	
Protocolo Wi-Fi	IEEE 802.11 b/g/n
Frecuencia Wi-Fi	2.4 GHz
Requerimientos de Wi-Fi	Secured Wi-Fi connection