



## Archer TX20U Plus



LED

Dimensiones

Antena

CARACTERÍSTICAS INALÁMBRICAS

Estándares Inalámbricos

Tasa de Señal

Status

84 × 156.3 × 19.2 mm (3.3 × 6.2 × 0.76 in)

2× High-Gain Dual-Band Antennas

IEEE 802.11a/b/g/n/ac/ax

5 GHz:

11ax: Up to 1201 Mbps(dynamic)

11ac: Up to 867 Mbps(dynamic)

11n: Up to 300 Mbps(dynamic)

11a: Up to 54 Mbps(dynamic)

2.4 GHz:

11ax: Up to 574 Mbps(dynamic)

11n: Up to 400 Mbps(dynamic)

11g: Up to 54 Mbps(dynamic)

11b: Up to 11 Mbps(dynamic)

Sensibilidad de Recepción

5 GHz:

11ax HE80 MCS0: -90 dBm

11ax HE80 MCS11: -59 dBm

11a 54Mbps: -77 dBm

11ac VHT80 MCS0: -92dBm

11ac VHT80 MCS9: -64dBm

2.4 GHz:

11ax HE40 MCS0: -94 dBm

11ax HE40 MCS11: -66 dBm

11g 54Mbps: -79 dBm

11n HT40 MCS9: -74dBm

Potencia de Transmision

5 GHz: 19dBm(FCC) /16dBm(CE) (EIRP)

2.4 GHz : 19dBm(FCC) / 14.5dBm(CE) (EIRP)

Modos Inalámbricos

Infrastructure mode

Seguridad Inalámbrica

WEP, WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK

OTROS

Certificacion

FCC, CE, RoHS

|                                    |                                                                                                                                                                                              |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Contenidos del Paquete             | AX1800 Dual Antennas High Gain Wireless USB Adapter<br>Archer TX20U Plus<br>Quick Installation Guide<br>1-meter USB 3.0 Cable                                                                |
| Requisitos del Sistema<br>Ambiente | Supported operating systems include Windows 10, 11<br>Operating Temperature: 0°C~40°C (32°F ~104°F)<br>Operating Humidity: 10%~90% non-condensing<br>Storage Humidity: 5%~90% non-condensing |