



TG-3468

CARACTERÍSTICAS DE HARDWARE

Estándares y Protocolos Interface

IEEE 802.3, 802.3u, 802.3ab, 802.3x, 802.1q, 802.1p,
CSMA/CD, TCP/IP
32-bit PCI Express
1 10/100/1000Mbps RJ45 port

Medios de Red

10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
EIA/TIA-568 100Ω STP (maximum 100m)

100BASE-TX: UTP category 5, 5e cable (maximum 100m)
EIA/TIA-568 100Ω STP (maximum 100m)

LED

1000Base-T: UTP category 5, 5e cable (maximum 100m)
Status

Estándares Inalámbricos Velocidad de Datos

IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3x
10/100/1000Mbps for Half-Duplex mode
20/200/2000Mbps for Full-Duplex mode

Indicador LED

1000Mbps Link/Act, 100Mbps Link/Act, 10Mbps Link/Act

Dimensiones

3.1 × 4.8 × 0.8 in (78.5 × 120.8 × 21.5mm)

Control de Flujo

IEEE 802.3x Flow Control (Full-Duplex)

OTROS

Certificacion

CE, FCC, RoHS

Contenidos del Paquete

Gigabit PCI Express Network Adapter TG-3468

Resource CD

Quick Installation Guide

Windows 7(32/64bits), Windows Vista(32/64 bits), Window
XP(32/64bits)

Requisitos del Sistema

Ambiente

Operating Temperature: 0°C~40°C (32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing