



TL-POE150S

CARACTERÍSTICAS DE HARDWARE

Interface

2 10/100/1000Mbps RJ45 Port
AUTO Negotiation/AUTO MDI/MDIX

Medios de Red

1 48VDC POWER INPUT PORT
10BASE-T: UTP category 3, 4, 5 cable (Max 100m)
EIA/TIA-568 100Ω STP (Max 100m)
100BASE-TX: UTP category 5, 5e cable (Max 100m)
EIA/TIA-568 100Ω STP (Max 100m)
1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)
15.4W (Max. 48VDC)

Fuente de Alimentación

Indicador LED

PWR

Dimensiones (W X D X H)

3.2*2.1*0.9 in.(80.8*54*24 mm)

CARACTERÍSTICAS DE SOFTWARE

Función básica

Compatible With IEEE 802.3af Compliant PDs
Delivers Power Up To 100 Meters
Auto-Determine The Necessary Power Requirements

OTROS

Certificacion

FCC, CE, RoHS

Contenidos del Paquete

Gigabit PoE Injector TL-POE150S
Power Adapter
RJ45 Cable
Installation Guide

Requisitos del Sistema

Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7,
MAC® OS, NetWare®, UNIX® or Linux.

Ambiente

Operating Temperature: 0°C~40°C (32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing