



TL-R470T+



CARACTERÍSTICAS DE HARDWARE

Estándares y Protocolos Interface

IEEE 802.3, 802.3u, 802.3x, TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP, HTTP, DDNS
1 Fixed Ethernet WAN Port
1 Fixed Ethernet LAN Port
3 Changeable Ethernet WAN/LAN Ports
10BASE-T: UTP category 3, 4, 5 cable (Max 100m), 100BASE-TX:

Medios de Red

UTP category 5, 5e cable (Max 100m)

Botón

Reset Button

Fuente de Alimentación

Internal Universal Power Supply
AC100-240V~50/60Hz input

Flash

4MB

DRAM

64MB

LED

PWR, SYS, WAN, LAN, WAN/LAN

Dimensiones (W X D X H)

8.2*5.0*1.0in. (209*126*26mm)

RENDIMIENTO

Sesiones Concurrentes

10000

FUNCIONES BÁSICAS

WAN Connection Type

Static/Dynamic IP, PPPoE, PPTP, L2TP, Dual Access, Bigpond Cable

MAC Clone

Modify WAN/LAN MAC Address

DHCP

DHCP Server/Client, DHCP Address Reservation

Configuración Switch

Port Mirror, Rate Control, Port Configuration, Port VLAN

FUNCIONES AVANZADAS

ACL

IP/MAC/URL/WEB Filtering

IGMP

IGMP Proxy/IGMP Snooping

Forwarding

Virtual Server, Port Triggering, DMZ

Equilibrio de carga

Policy Routing, Link Backup

Routing

Static Routing

Seguridad

FTP/SIP/PPTP/IPsec/H.323 ALG, DoS Defence, Ping of Death, IP/MAC Binding

Control de Trafico

Bandwidth Control, Session Limit

ADMINISTRACIÓN

Servicio	PPPoE Server, E-Bulletin, Dynamic DNS, UPnP
Mantenimiento	Time Setting, Daylight Saving Time, SNMP, Diagnostics, Firmware Upgrade, Factory Defaults/Reboot, Backup/Restore, System Log, Remote Management, Statistics
OTROS	
Certificacion	CE, FCC, RoHS
Contenidos del Paquete	TL-R470T+ Power Cord RJ-45 Ethernet Cable Quick Installation Guide Resource CD
Requisitos del Sistema	Microsoft® Windows® 8, 7, Vista™, XP or MAC® OS, NetWare®, UNIX® or Linux
Ambiente	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing