



TL-MR3420



CARACTERÍSTICAS DE HARDWARE

Interface 1 USB 2.0 Port for
LTE/HSPA+/HSUPA/HSDPA/UMTS/EVDO USB Modem

Botón 1 10/100Mbps WAN Port, 4 10/100Mbps LAN Ports,
support the auto-Negotiation and auto-MDI/MDIX
WPS/Reset Button
Wireless On/Off Switch
Power On/Off Button

Fuente de Alimentación Externa 12VDC/1A

Dimensiones (W X D X H) 8*5.4*1.7 in. (204*138*44 mm)

Tipo de Antena Omni directional, Detachable, Reverse SMA

Ganancia de Antena 2x5dBi

CARACTERÍSTICAS INALÁMBRICAS

Estándares Inalámbricos IEEE 802.11b, IEEE 802.11g, IEEE 802.11n

Frecuencia 2.4-2.4835GHz

Potencia de Transmision <20dBm

Seguridad Inalámbrica Support 64/128 bit WEP, WPA-PSK/WPA2-PSK,
Wireless MAC Filtering

CARACTERÍSTICAS DE SOFTWARE

Seguridad NAT Firewall, SPI Firewall, MAC / IP / Packet /
Application / URL Filtering, Denial of Service(DoS), SYN
Flooding, Ping of Death

Administración Web Based Configuration(HTTP), Web Based Firmware
Upgrade

OTROS

Certificacion CE, FCC, RoHS

Contenidos del Paquete 3G/4G Wireless N Router TL-MR3420

2 Antennas

Power supply unit

Ethernet Cable

Resource CD

Requisitos del Sistema
Ambiente

Quick Installation Guide

Microsoft® Windows® 98SE, NT, 2000, XP, Vista™
Windows 7, 8, 10, MAC® OS, NetWare®, UNIX® or
Linux.

Operating Temperature: 0°C~40°C (32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing