



RE305

CARACTERÍSTICAS DE HARDWARE

Tipo de Enchufe

EU, UK, US

Estándares y Protocolos

IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11a, IEEE 802.11b

Interface

1 x 10/100M Ethernet Port (RJ45)

Botón

WPS Button, Reset Button

Consumo de Energía

7.3W (max power consumption)

Dimensiones (W X D X H)

3.1 x 3.0 x 3.0 in. (80 x 78 x 77mm)

Antena

2 x external

CARACTERÍSTICAS INALÁMBRICAS

Frecuencia

2.4GHz & 5GHz(11ac)

Tasa de Señal

5GHz:Up to 867Mbps

2.4GHz:Up to 300Mbps

Sensibilidad de Recepción

5GHz :

11a 6Mbps:-91dBm@10% PER

11a 54Mbps: -74dBm@10% PER

11ac HT20 mcs8: -68dBm@10% PER

11ac HT40 mcs9: -63dBm@10% PER

11ac HT80 mcs9: -59dBm@10% PER

2.4GHz

11g 54M: -79dBm@10% PER

11n HT20 mcs7: -77dBm@10% PER

11n HT40 mcs7: -74dBm@10% PER

Modos Inalámbricos

Range Extender/Access Point

Wireless Statistic

Funciones Inalámbricas

Concurrent Mode boost both 2.4G/5G Wi-Fi band

Wireless Statistic

Concurrent Mode boost both 2.4G/5G Wi-Fi band

Access Control

LED Control

Seguridad Inalámbrica	Domain Login Function 64/128-bit WEP WPA-PSK / WPA2-PSK
Potencia de Transmisión	<17dBm(2.4GHz) <17dBm(5GHz)
OTROS	
Certificacion	CE, FCC, RoHS
Contenidos del Paquete	AC1200 Wi-Fi Range Extender RE305 Quick Installation Guide
Dimensiones de la Caja (W X D X H)	6.15 x 4 x 3.7 in. (156.5 x 101.5 x 95mm) Microsoft® Windows® 98SE, NT, 2000, XP, Vista or Windows 7, 8, 10, Mac® OS, NetWare®, UNIX® or Linux.
Requisitos del Sistema	
Ambiente	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

