



EAP110-Outdoor

CARACTERÍSTICAS DE HARDWARE

Interface	Fast Ethernet (RJ-45) Port *1 (Support Passive PoE)
Botón	Reset
Fuente de Alimentación	24V Passive PoE (+4,5pins; -7,8pins. PoE Adapter Included)
Consumo de Energía	3.12 W
Dimensiones (W X D X H)	8.5 × 1.8 × 1.1 in. (216 × 46 × 27 mm)
Tipo de Antena	2*3dBi External Omni waterproof
Resistencia a la Intemperie	IP65
Montaje	Pole / Wall Mounting (Kits included)

CARACTERÍSTICAS INALÁMBRICAS

Estándares Inalámbricos	IEEE 802.11n/g/b
Frecuencia	2.4GHz
Tasa de Señal	11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
Potencia de Transmision	CE : ≤20dBm (EIRP) FCC: ≤22dBm
Funciones Inalámbricas	Multiple SSIDs (Up to 8 SSIDs) Enable/Disable Wireless Radio Automatic Channel Assignment Transmit Power Control (Adjust Transmit Power on dBm) QoS(WMM) Load Balance Rate Limit Reboot Schedule Wireless Schedule Wireless Statistics based on SSID/AP/Client Captive Portal Authentication
Seguridad Inalámbrica	

	Access Control
	Wireless Mac Address Filtering
	Wireless Isolation Between Clients
	SSID to VLAN Mapping
	Rogue AP Detection
	802.1X Support
	64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
ADMINISTRACIÓN	
Omada Cloud Access	Yes
Omada App	Yes
Omada Cloud Controller	Yes
Centralized Management	• Omada Cloud-Based Controller • Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller
Omada Controller Software	Yes
Cloud Access	Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Alertas de Correo Electrónico	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	Yes
System Logging Local/Remote Syslog	Local/Remote Syslog
SSH	Yes
Web-based Management	HTTP/HTTPS
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes
OTROS	
Certificacion	CE, FCC, RoHS
Contenidos del Paquete	300Mbps Wireless N Outdoor Access Point, EAP110- Outdoor Passive PoE Adapter Power Cord Mounting Kits Waterproof Rubber Insert Waterproof Antennas Installation Guide Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10 Operating Temperature: -30°C~65°C (-22°F~149°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Requisitos del Sistema	
Ambiente	