



EAP115

CARACTERÍSTICAS DE HARDWARE

Interface

Botón

Fuente de Alimentación

Consumo de Energía

Dimensiones

Tipo de Antena

Montaje

Fast Ethernet (RJ-45) Port *1 (Support IEEE802.3af PoE)

Reset

PoE or external 9VDC/0.6A power supply

2.8W

7.5×6.8×1.2 in. (189.4×172.3×29.5mm)

Internal 2* 4dBi Omni

Ceiling /Wall Mounting (Kits included)

CARACTERÍSTICAS INALÁMBRICAS

Estándares Inalámbricos

Frecuencia

Tasa de Señal

Sensibilidad de Recepción

IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

2.4-2.4835GHz

11n: Up to 300Mbps(dynamic)

11g: Up to 54Mbps(dynamic)

11b: Up to 11Mbps(dynamic)

300M: -71dBm@10% PER

150M: -75dBm@10% PER

54M: -78dBm@10% PER

11M: -93dBm@8% PER

6M: -92dBm@10% PER

1M: -96dBm@8% PER

Funciones Inalámbricas

Multiple SSIDs (Up to 8 SSIDs)

Enable/Disable Wireless Radio

Automatic Channel Assignment

Transmit Power Control (Adjust Transmit Power on dBm)

QoS(WMM)

Rate Limit

Reboot Schedule

Wireless Schedule

Seguridad Inalámbrica	Wireless Statistics based on SSID/AP/Client Captive Portal Authentication Access Control Wireless MAC Address Filtering Wireless Isolation Between Clients SSID to VLAN Mapping Rogue AP Detection 802.1X Support 64/128/152-bit WEP / WPA / WPA2-Enterprise,WPA-PSK / WPA2-PSK
Potencia de Transmisión	CE: ≤19dBm(EIRP) FCC: ≤21dBm
ADMINISTRACIÓN	
Omada App	Yes
Centralized Management	• Omada Cloud-Based Controller • Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller
Omada Controller Software	Yes Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Cloud Access	Yes
Alertas de Correo Electrónico	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1,v2c
System Logging Local/Remote Syslog	Local/Remote Syslog
Telnet	Yes
SSH	Yes
Web-based Management	HTTP/HTTPS
Management VLAN	Yes
OTROS	
Certificacion	CE, FCC, RoHS
Contenidos del Paquete	300Mbps Wireless N Ceiling Mount Access Point EAP115 Power Adapter Mounting Kits, Installation Guide
Requisitos del Sistema	Microsoft Windows 10/8/7/Vista/XP

Ambiente

Operating Temperature: 0°C~40°C
(32°F~104°F)

Storage Temperature: -40°C~70°C (-
40°F~158°F)

Operating Humidity: 10%~90% non-
condensing

Storage Humidity: 5%~90% non-
condensing