

MERCUSYS®

MW330HP

Wireless

Wireless Standards

IEEE 802.11b/g/n

Frequency

2.402-2.482GHz

Signal Rate

11n: Up to 300Mbps (Dynamic)

11g: Up to 54Mbps (Dynamic)

11b: Up to 11Mbps (Dynamic)

Reception Sensitivity

270M: -74dBm@10% PER

130M: -76dBm@10% PER

54M: -78dBm@10% PER

11M: -90dBm@10% PER

6 M: -94dBm@10% PER

1 M: -96dBm@10% PER

Transmission Power



<20dBm (EIRP)

Wireless Security

WPA-PSK / WPA2-PSK

Wireless Functions

Enable/Disable Wireless Radio, WDS Bridging

Software

WAN Type

Dynamic IP/Static IP/PPPoE/PPTP/L2TP

Management

Access Control

Local Management

Remote Management

DHCP

Server

Port Forwarding

Virtual Server, UPnP, DMZ

Firewall Security

IP and MAC Address Binding

Guest Network

2.4GHz Guest Network

Hardware

Dimensions (W X D X H)

192mm×127mm×36mm

Interfaces

3*10/100Mbps LAN Ports

1*10/100Mbps WAN Port

Button

TURBO, WPS/RESET

External Power Supply

9V/0.6A

Antenna Type

3 * 7dBi

Others

Package Contents

300Mbps High Power Wireless N Router
(MW330HP)

Power Adapter
Quick Installation Guide
Ethernet Cable

Environment

Operating Temperature: 0°C~40°C (32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% Non-Condensing

Storage Humidity: 5%~90% Non-Condensing