ASUS Introduces the DUAL-RTX4070S-O12G-EVO-WHITE Graphics Card

Item Name: ASUS Dual GeForce RTX™ 4070 SUPER EVO White OC Edition (PCIe 4.0, 12GB GDDR6X, DLSS 3, HDMI 2.1a, DisplayPort 1.4a, 2.5-slot design, Axial-tech fan design, Dual BIOS)

50 Word: The SFF-ready ASUS Dual GeForce RTX™ 4070 SUPER EVO White OC Edition fuses dynamic thermal performance with broad compatibility. Advanced cooling solutions from flagship graphics cards — including two Axial-tech fans for maximizing airflow to the heatsink — are packed into the 22.7 cm long, 2.5-slot card, delivering more power in less space. These enhancements make ASUS Dual the perfect choice for gamers who want heavyweight graphics performance in a compact build.

- Model Name: DUAL-RTX4070S-O12G-EVO-WHITE
- ETA: In stock
- Web Link: https://www.asus.com/motherboards-components/graphics-cards/dual/dual-rtx4070s-o12g-evo-white/
- Product Image Link: https://www.dropbox.com/scl/fo/jx8ig9jqwj2sk64pbgqry/ADonalKUx0_onCkjTd4jrbY?rlkey=6abszkzcmiu86o8ol5vq25an9&e=1&st=6f7aq2nr&dl=0
- Video Link: N/A
- MSRP: $629.99
- Part Number: 90YV0KC8-M0AA00

- **UPC Code:** 197105650749
- **Box Dimension:** 14.33" x 8.62" x 2.64"
- **Gross Weight:** 2.73 lbs
- **Quantity per Carton:** 8 pieces
- **Cartons per Pallet:** 25 cartons/pallet
- **Quantity per Pallet:** 200 pieces/pallet
- **Warranty:** 3 Year Warranty

[Graphics Card- DUAL-RTX4070S-O12G-EVO-WHITE]

< Product Specification Summary >

- **Powered by NVIDIA DLSS3**, ultra-efficient Ada Lovelace arch, and full ray tracing

- **4th Generation Tensor Cores:** Up to 4X performance with DLSS 3 vs. brute-force rendering

- **3rd Generation RT Cores:** Up to 2X ray tracing performance

- **SFF-Ready Enthusiast GeForce Card** for small-form-factor builds

- **OC edition:** Boost Clock 2550 MHz (OC Mode)/ 2520 MHz (Default Mode)

- **Axial-tech fan design** features a smaller fan hub that facilitates longer blades and a barrier ring that increases downward air pressure

- A **2.5-slot design** maximizes compatibility and cooling efficiency for superior performance in small chassis

- **0dB technology** lets you enjoy light gaming in relative silence

- **Dual ball fan bearings** can last up to twice as long as sleeve bearing designs

- **Auto-Extreme** precision automated manufacturing for higher reliability

< Product Specification >

Specifications

Model Name	DUAL-RTX4070S-O12G-EVO-WHITE
Graphics Engine	NVIDIA® GeForce RTX™ 4070 SUPER
CUDA Cores	7168
OpenGL®	OpenGL® 4.6
Engine Clock	OC mode : 2550 MHz (Boost Clock) Default mode : 2520 MHz (Boost Clock)
Memory Interface	192-bit
Video Memory	12GB GDDR6X
Memory Clock	21 Gbps
Power Connector	1 x 16-pin
I/O	1 x Native HDMI 2.1a 3 x Native DisplayPort 1.4a
HDCP Compliant	HDCP 2.3
Digital Max. Resolution	7680 x 4320
Maximum Display Support	4
NVLink/Crossfire Support	N/A
Recommended PSU	750W
Bus Standard	PCIE 4.0
Package Contents	1 x Speedsetup Manual 1 x Thank you card 1 x Adapter Cable (1 to 2)
Software Bundled	ASUS GPU Tweak III & GeForce Game Ready Driver & Studio Driver: please download all software from the support site.
Slot	2.5 slot
Dimension	
Card Size (mm/inch)	227.2 x 123.24 x 49.6 mm 8.94 x 4.85 x 1.95 inch
Color Box (mm)	368 x 220.5 x 68 mm
Weight	
Single Card (KG)	0.687 KG
Product Weight (with packing) (KG)	1.24 KG
Note	* Our wattage recommendation is based on a fully overclocked GPU and CPU system configuration. For a more tailored suggestion, please use the "Choose By Wattage" feature on our PSU product page: https://rog.asus.com/event/PSU/ASUS-Power-Supply-Units/index.html * All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets. If you do not use the latest and current specifications of ASUS products, you shall be liable for all loss and damage claimed by third party to ASUS based on false advertising or any other issues caused from using false specifications of ASUS products.

California Proposition 65

⚠️**WARNING** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.