GeForce RTX™ 5080 16G INSPIRE 3X OC







SPECIFICATIONS

Marketing Name	GeForce RTX™ 5080 16G INSPIRE 3X OC
Memory	16GB GDDR7
Motor de gráficos	NVIDIA [®] GeForce RTX [™] 5080
Norma Bus	PCI Express [®] Gen 5
Interfaz de Memoria	256-bit
Velocidad clock núcleo (MHz)	Extreme Performance: 2655 MHz (MSI Center) Boost: 2640 MHz
Velocidad clock memoria (MHz)	30 Gbps
Máximo de pantallas	4
Tecnología G-SYNC™	<u>Y</u>
Salida	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Soporte HDCP	Υ
Consumo (W)	360W
Alimentación recomendada (W)	850W
Resolución máxima digital	7680 x 4320
Conectores de alimentación	16-pin x1
Soporte DirectX Versión	12 Ultimate
Soporte OpenGL Versión	4.6
Dimensiones (mm)	288 x 112 x 50 mm

CONNECTIONS



- 1. DisplayPort
- 2. HDMI™

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickelplated copper baseplate and transferred.



Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Metal Backplate

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Air Antegrade Fin

Fins with a V-shaped cutout are located at the airflow passthrough to improve flow efficiency.



Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Take full control with the most recognized and widely used graphics card overclocking software in the world.