



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5090 32G SUPRIM SOC
Model Name	G5090-32SPS
Cores	21760 Units
Memory	32GB GDDR7
Memory Bus	512-bit
Power connectors	16-pin x 1
Recommended PSU	1000 W
Motor Gráfico	NVIDIA® GeForce RTX™ 5090
Bus Standard	PCI Express® Gen 5 x16
Card Dimension (mm)	359 x 150 x 76 mm
DirectX Version Support	12 Ultimate
Reloj de Núcleo	Gaming Mode: Extreme Performance: 2580 MHz (MSI Center) Boost: 2565 MHz
Velocidad de Memoria	Silent Mode: Extreme Performance: 2527 MHz (MSI Center) Boost: 2512 MHz
Maximum Displays	28 Gbps
G-SYNC™ technology	4
Output	Y
Soporte HDCP	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Power consumption (W)	Y
Digital Maximum Resolution	Gaming mode: 600 W Silent mode: 575 W
Versión Soportada de OpenGL	7680 x 4320
Peso	4.6
	2840 g / 3695 g

CONNECTIONS

FEATURES



HYPER FROZR THERMAL DESIGN

An apex evolution of advanced thermal design that delivers unparalleled cooling and quiet operation.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.




Advanced Vapor Chamber

Built-in Vapor Chamber swiftly transfers heat from the GPU and VRAM to the core pipe for optimal dissipation.



Optimized Heat Distribution - Core Pipe

Square-shaped Core Pipes maximize heat dissipation with the Vapor Chamber for superior cooling.



Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.




Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



1. DisplayPort
2. HDMI™