

SPECIFICATIONS

Getttech®



GAC-24407G COLORFUL WIRELESS MOUSE RATÓN INALÁMBRICO

MOUSE SPECIFICATIONS	
Size	Length: 4.09in ± 0.50mm Width: 2.60in ± 0.50mm Height: 1.57in ± 0.50mm
Weight	0.19 lbs ± 5g (without battery)
Material	Button: ABS DPI Button: ABS Wheel: PC Middle Case: ABS+Silicon Gel Bottom Case: ABS Leather Case: Silicon
Rated Power	Operating Voltage: 1.5V DC Working Current: +1.5V DC Hour ≤25mA First Level Sleep Current: Instant Entry 0.34-0.45mA Secondary Sleep Current: (After 20 seconds) 0.15-0.3mA Three Level Sleep Current: (After 15 minutes) Less than or equal to 0.03mA
Distance	393.70 in
Buttons	Left and Right Button, DPI Switch Button + Wheel
Optical Light	0.5 LED red
Resolution	600-1200-1600DPI
Compatibility	USB Specification Version 1.1, Version 2.0 or higher
System Requirements	Support for Windows 7/8/10/XP/2000/Vista/ Mac operating system
USB RECEIVER SPECIFICATIONS	
Size	Length: 0.73in ± 0.20mm Width: 0.52in ± 0.15mm Height: 0.21in ± 0.15mm
Weight	0.003 lbs ± 0.1g
Material	FR-4
Interface	USB
Rated Power	Working Voltage: 4.20V ~ 5.25V DC Working Current: 25mA (Max)
Operation Channel	16
Transmission Rate	2Mbps
Maximum Use Distance	393.70 in
SAN 18	7503028761678

ESPECIFICACIONES

GAC-24407G COLORFUL WIRELESS MOUSE RATÓN INALÁMBRICO

Getttech®



ESPECIFICACIONES DEL RATÓN	
Medidas	Longitud: 104.01±0.50mm Anchura: 66.26±0.50mm Altura: 40.01±0.50mm
Peso	90g± 5g (Sin Pila)
Materia	Botones: ABS Botón DPI: ABS Rueda: PC Carcasa Superior: ABS+ Gel de Silicona Carcasa Inferior: ABS Fondo de Pie: Silica
Potencia Nominal	Tensión de funcionamiento: 1.5V CC Corriente de Operación: +1.5V CC Hora <25mA Corriente de Reposo de Primer Nivel: (Iniciada instantánea) 0.3-0.45mA Corriente Secundaria de Reposo: (Después de 20 Segundos) 0.15-0.3mA Corriente de Reposo en tres Etapas: (Después de 15 Segundos) Menos de o igual a 0.03mA
Distancia	10M
Botones	Botón Izquierdo y Derecho, Botón de Cambio DPI + Rueda
Luz Óptica	4x5 LED rojo
Resolución	800-1200-1600DPI
Compatibilidad	Especificación USB versión 1.1, versión 2.0 o superior
Requisitos del Sistema	Soporte para Windows 7/8/10/XP/2003/Vista/ Sistema Operativo Mac
ESPECIFICACIONES DEL RECEPTOR USB	
Medidas	Longitud: 18.59±0.20mm Anchura: 13.20±0.15mm Altura: 5.50±0.15mm
Peso	1.6±0.1g
Materia	PC+I
Interfaz	USB
Potencia Nominal	Tensión de Trabajo: 4.35V ~ 5.25V CC Corriente de Trabajo: 25mA (Max)
Canal de Operación	16
Velocidad de Transmisión	2Mbps
Distancia Máxima de Uso	10M
EAN 13	7503028761478