

NOMBRE DEL PRODUCTO: Tarjeta madre ASUS ROG STRIX B850-A GAMING WIFI

INFORMACIÓN GENERAL DEL PRODUCTO

SKU: ROG STRIX B850-A GAMING WIFI

No. parte: 90MB1J50-M0AAY0

Código UPC: 197105772670

Dimensiones: 13.9 x 10.75 x 2.68 inch

Peso bruto: 3.88 lb

Garantía: 3 años

Enlace de descarga de imágenes:

<https://www.dropbox.com/scl/fo/j03fudept9750vl3ymz7e/ALqZ9JqzbKRcZRZI-6DI-H8?rlkey=goyi2l1c9j2em4l38ai360vwq&st=y2cpt4ql&dl=0>



INFORMACIÓN PARA EL ALTA WEB DEL PRODUCTO

[Título largo:] Tarjeta madre ASUS ROG STRIX B850-A GAMING WIFI ATX AM5 para AMD Ryzen, DDR5, PCIe 5.0, WiFi 7, 4x M.2, USB 20Gbps Tipo-C, Lista para IA

[Título corto:] Tarjeta madre ASUS ROG STRIX B850-A GAMING WIFI ATX AM5 para AMD Ryzen, DDR5, PCIe 5.0, WiFi 7, lista para IA

[Puntos clave/ Características:]

- Preparado para la informática de IA avanzada: Diseñados para el futuro de la informática de IA, con la potencia y conectividad necesarias para las exigentes aplicaciones de IA.
- Zócalo AMD AM5: Preparado para los procesadores de sobremesa AMD Ryzen™ series 9000, 8000 y 7000
- Control inteligente: ASUS AI Advisor, AI Networking II y AEMP para simplificar la configuración y mejorar el rendimiento
- Solución de alimentación robusta: Solución de alimentación 14+2+2 clasificada para 80A por etapa con un conector de alimentación ProCool de 8+8 pines, choques de aleación de alta calidad y condensadores duraderos para soportar procesadores multinúcleo
- Diseño térmico optimizado: Disipadores térmicos masivos conectados a los VRM con almohadillas térmicas de alta conductividad y una cubierta de E/S integrada
- Soporte M.2 de última generación: Una ranura M.2 PCIe® 5.0 integrada y tres ranuras M.2 PCIe 4.0, todas con importantes soluciones de refrigeración



- Conectividad abundante: USB 20 Gbps Type-C®, USB 10 Gbps Type-C®, conector del panel frontal USB 10 Gbps Type-C®, seis puertos USB 5 Gbps adicionales, PCIe 5.0 x16 SafeSlots, puerto HDMI™ y puerto DisplayPort
- Redes de alto rendimiento: WiFi 7 (802.11be) integrado con Ethernet Intel de 2,5 Gb
- Diseño DIY amigable: Ranura PCIe Q-Release Slim, M.2 Q-Latch, M.2 Q-Release, M.2 Q-Slide, Q-Antenna, Q-Dashboard, Q-LED, botón BIOS FlashBack™, botón Clear CMOS y escudo de E/S premontado
- Audio inmersivo: Códec ROG SupremeFX ALC4080 con amplificador Savitech SV3H712, junto con Dolby Atmos®.

[Keywords:]

Motherboard, ASUS, Tarjeta, placa, madre, base, AM5, AMD, Intel, B850, B860, chipset, TUF, streaming, gaming, Edición, Fotografía, juegos, LGA1700, LGA1851, Ryzen, Core, Ultra, nueva, B650, X870, overclock, DDR5, RAM, USB, WiFi, ia, EXPO, XMP DCCP, RGB, ARGB, Aura, PCI, NVME, SATA, AM4, TUF, LAN, entretenimiento, esports

ESPECIFICACIONES TÉCNICAS

ROG STRIX B850-A GAMING WIFI

Note: The specifications are subject to change without notice.

CPU	AMD Socket AM5 for AMD Ryzen™ 9000 & 8000 & 7000 Series Desktop Processors* * Refer to https://www.asus.com/support/download-center/ for CPU support list.
Chipset	AMD B850 Chipset
Memory	4 x DIMM slots, max. 192GB, DDR5 Supports up to 8000+MT/s(OC) with Ryzen™ 9000 & 8000 & 7000 Series Processors ECC and Non-ECC, Un-buffered DIMM Dual channel memory architecture Supports AMD Extended Profiles for Overclocking (EXPO™) ASUS Enhanced Memory Profile (AEMP) * Supported memory types, data rate (speed), and number of DRAM modules vary depending on the CPU and memory configuration, for more information please refer to CPU/Memory Support list under the Support tab of product information site or visit https://www.asus.com/support/download-center/ .

	** Non-ECC, un-buffered DDR5 memory supports On-Die ECC function.
Graphics	1 x DisplayPort* 1 x HDMI™ port** - Graphics specifications may vary between CPU types. Please refer to AMD CPU specifications. * Supports max. 8K@30Hz as specified in DisplayPort 1.4 ** Supports 4K@60Hz as specified in HDMI 2.1 *** VGA resolution support depends on processors' or graphic cards' resolution.
Expansion Slots	AMD Ryzen™ 9000 & 7000 Series Desktop Processors 1 x PCIe 5.0 x16 slot with Q-Release Slim AMD Ryzen™ 8000 Series Desktop Processors 1 x PCIe 5.0 x16 slot with Q-Release Slim (supports PCIe 4.0 x8/x4 mode)** AMD B850 Chipset 1 x PCIe 4.0 x16 slot (supports x4 mode)* * PCIe x16(G4) slot (supports x4 mode) from AMD B850 Chipset shares bandwidth with M.2_3 ** Specifications vary by CPU types. - To ensure compatibility of the device installed, please refer to https://www.asus.com/support/download-center/ for the list of supported peripherals.
Storage	Total supports 4 x M.2 slots and 2 x SATA 6Gb/s ports AMD Ryzen™ 7000 & 9000 Series Desktop Processors M.2_1 (Key M), type 2242/2260/2280 (supports PCIe 5.0x4 mode) M.2_2 (Key M), type 2280/22110 (supports PCIe 4.0 x4 mode) AMD Ryzen™ 8000 Series Desktop Processors M.2_1 (Key M), type 2242/2260/2280 (supports PCIe 4.0x4 mode) M.2_2 (Key M), type 2280/22110 (supports PCIe 4.0 x4/x2 mode)*

	AMD B850 Chipset M.2_3 (Key M), type 2280 (supports PCIe 4.0 x4)** M.2_4 (Key M), type 2280 (supports PCIe 4.0 x4) 2 x SATA 6Gb/s ports * Specifications vary by CPU types. ** M.2_3 slot shares bandwidth with PCIEX16(G4). When PCIEX16(G4) slot is operating, M.2_3 will be disabled. AMD RAIDXpert2 Technology Ryzen™ 9000 Series Processors: RAID 0/1/5/10 Ryzen™ 8000 Series Processors: RAID 0/1 Ryzen™ 7000 Series Processors: RAID 0/1/10
Ethernet	1 x Intel® 2.5Gb Ethernet ASUS LANGuard
Wireless & Bluetooth®	Wi-Fi 7* 2x2 Wi-Fi 7 (802.11be) Supports 2.4/5/6GHz frequency band** Supports Wi-Fi 7 160MHz bandwidth, up to 2.9Gbps transfer rate. Bluetooth® v5.4*** *Wi-Fi features may vary depending on the operating system For Windows 11, Wi-Fi 7 will require 24H2 or later version for full functions, Windows 11 21H2/22H2/23H2 only supports Wi-Fi 6E. For Windows 10, only Wi-Fi 6 is supported. ** Wi-Fi 6GHz frequency band and bandwidth regulatory may vary between countries. *** The Bluetooth® version may vary, please refer to the Wi-Fi module manufacturer's website for the latest specifications.
USB	Rear USB (Total 10 ports) 1 x USB 20Gbps port (1 x USB Type-C®) 3 x USB 10Gbps ports (2 x Type-A + 1 x USB Type-C®) 4 x USB 5Gbps ports (4 x Type-A) 2 x USB 2.0 ports (2 x Type-A) Front USB (Total 7 ports)

	1 x USB 10Gbps connector (supports USB Type-C®) 1 x USB 5Gbps header supports 2 additional USB 5Gbps ports 2 x USB 2.0 headers support 4 additional USB 2.0 ports * USB Type-C® power delivery output: max. 5V/3A
Audio	ROG SupremeFX 7.1 Surround Sound High Definition Audio CODEC ALC4080* - Impedance sense for front and rear headphone outputs - Supports: Jack-detection, Multi-streaming, Front Panel MIC Jack-retasking - High quality 120 dB SNR stereo playback output and 110 dB SNR recording input - Supports up to 32-Bit/384 kHz playback on front panel Audio Features - SupremeFX Shielding Technology - Savitech SV3H712 AMP - Rear optical S/PDIF out port - Premium audio capacitors - Audio cover * A chassis with an HD audio module in the front panel is required to support 7.1 Surround Sound audio output. ** The LINE OUT port on the rear panel does not support spatial audio. If you wish to use spatial audio, make sure to connect your audio output device to the audio jack on the front panel of your chassis or use a USB interface audio device.
Back Panel I/O Ports	1 x USB 20Gbps port (1 x USB Type-C®) 3 x USB 10Gbps ports (2 x Type-A + 1 x USB Type-C®) 4 x USB 5Gbps ports (4 x Type-A) 2 x USB 2.0 ports (2 x Type-A) 1 x DisplayPort 1 x HDMI™ port 1 x Wi-Fi module 1 x Intel® 2.5Gb Ethernet port

	2 x Audio jacks 1 x Optical S/PDIF out port 1 x BIOS FlashBack™ button 1 x Clear CMOS button
Internal I/O Connectors	Fan and Cooling Related 1 x 4-pin CPU Fan header 1 x 4-pin CPU OPT Fan header 1 x 4-pin AIO Pump header 4 x 4-pin Chassis Fan headers Power Related 1 x 24-pin Main Power connector 2 x 8-pin +12V CPU Power connector Storage Related 4 x M.2 slots (Key M) 2 x SATA 6Gb/s ports USB 1 x USB 10Gbps connector (supports USB Type-C®) 1 x USB 5Gbps header supports 2 additional USB 5Gbps ports 2 x USB 2.0 headers support 4 additional USB 2.0 ports Miscellaneous 3 x Addressable Gen 2 headers 1 x CPU Over voltage jumper 1 x Front Panel Audio header (F_AUDIO) 1 x Power button 1 x 10-1 pin Front System Panel header 1 x Thermal Sensor header 1 x Thunderbolt™ (USB4®) header
Special Features	Extreme Engine Digi+ - 5K Black metallic capacitors

	ASUS Q-Design - M.2 Q-Latch - M.2 Q-Release - M.2 Q-Slide - PCIe Slot Q-Release Slim (with PCIe SafeSlot) - Q-Antenna - Q-Dashboard - Q-DIMM - Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green]) - Q-Slot ASUS Thermal Solution - M.2 heatsink backplate - M.2 heatsink ASUS EZ DIY - BIOS FlashBack™ button - BIOS FlashBack™ LED - Clear CMOS button - ProCool - Pre-mounted I/O shield - SafeSlot - SafeDIMM Aura Sync - Addressable Gen 2 headers
Software Features	ROG Exclusive Software - ROG CPU-Z - Dolby Atmos ASUS Exclusive Software Armoury Crate - AIDA64 Extreme (60 days free trial)

	- Aura Creator - Aura Sync - GameFirst - HWiNFO - Power Saving - Fan Xpert 4 ASUS DriverHub ASUS GlideX TurboV Core Adobe Creative Cloud (Free Trial) Norton 360 for Gamers (60 Days Free Trial) WinRAR (40 Days Free Trial) UEFI BIOS ASUS EZ DIY - ASUS CrashFree BIOS 3 - ASUS EZ Flash 3 - ASUS UEFI BIOS EZ Mode - ASUS MyHotkey
BIOS	256 Mb Flash ROM, UEFI AMI BIOS
Manageability	WOL by PME, PXE
Accessories	Cables 2 x SATA 6Gb/s cables Miscellaneous 1 x ASUS WiFi Q-Antenna 1 x Cable ties package 1 x M.2 Q-Latch package 1 x M.2 Q-Slide package 1 x ROG key chain 1 x ROG Strix stickers



	4 x M.2 rubbers Documentation 1 x Quick start guide
Operating System	Windows 11
Form Factor	ATX Form Factor 12 inch x 9.6 inch (30.5 cm x 24.4 cm)