




# HYPER 620S

Cooler Master is advancing the Hyper Series legacy with the debut of the 6 heat pipe Hyper air cooler – the Hyper 620S. With the dual tower dual fan design, the 6 heat pipe array dissipates heat impressively to handle the newest CPUs in the market. The new fans display stunning color and lighting with easy clip to install. The cooler height is set to 154.9mm for a wide range of fitment for the majority of chassis without compromising cooling capabilities. The ARGB Auto Detection provides default ARGB spectrum lighting upon power up, or full ARGB customization through the motherboard header. We have expanded the Hyper line with an all new powerful introduction worthy of its name – Hyper 620S



## Dual Tower Heat Sink

Dual tower heat sink delivers twice the surface area for superior cooling



## 6 Heat Pipes Design

Complete CPU coverage nickel-plated base with 6 uniform heat pipes transfers heat evenly and quickly



## ARGB Auto Detection

Intuitive LED detection automatically provides default ARGB spectrum lighting or full ARGB customization via 3-pin header connection



## Broad Case Fitment

Low profile heat pipes optimized at 154.9mm height accommodates most RAM and case requirements

**ARGB Auto Detection** - Intuitive LED detection automatically provides default ARGB spectrum lighting or full ARGB customization via 3-pin header connection.

**Broad Case Fitment** - Low profile heat pipes optimized at 154.9mm height accommodates most RAM and case requirements.

**Dual Tower Heat Sink** - Dual tower heat sink and dual fans deliver twice the surface area for superior cooling.

**6 Heat Pipes Design** - Complete CPU coverage nickel-plated base with 6 uniform heat pipes transfers heat evenly and quickly.

## SPECIFICATIONS

Product NaRR-D6NA-17PA-R1 me	Hyper 620S	
Product Number	RR-D6NA-17PA-R1	
Exterior Color	Black/Silver	
CPU Socket	Intel® LGA 1700 / 1200 / 1151 / 1150 / 1155 / 1156 socket	
	AMD® AM5 / AM4 socket	
Dimensions (L x W x H)	125 x 137 x 154.9 mm	
Heat Sink Material	6 Heat Pipes/ Aluminum Fins	
Fan	Dimensions (L x W x H)	120 x 120 x 25mm
	Profile	Addressable RGB
	Quantity (pcs)	2 PCS
	Speed	650~1750 RPM ± 10%
	Airflow (Max)	71.93 CFM
	Pressure (Max)	1.86 mmH2O
	MTTF	>160,000 hours
	Noise Level (Max)	27.2 dB(A)
	Bearing	Rifle
	Power Connector	4-Pin PWM
	Rated Voltage	12 VDC
	Rated Current	0.26 A
	Safety Current	0.37 A
	Power Consumption	3.12 W
Warranty	2 years	

## PACKING INFORMATION

EAN code	4719512137956
UPC code	884102110276
Net weight	1.11 kg
Gross weight	1.57 kg
Package dimension (L x W X H)	17.3 x 15.9 x 20.3 cm
Carton dimension (L x W x H)	48.7 x 36.2 x 23.8 cm
Units/CTN	6

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	2880	48	N/A
40'	5760	48	N/A
40 HQ	6480	54	N/A