



TL-SL1218P

CARACTERÍSTICAS DE HARDWARE

Interface

- 16× PoE+ 10/100 Mbps RJ45 Ports
- 2× 10/100/1000 Mbps RJ45 Ports
- 1× Combo Gigabit SFP Slot

Medios de Red

- 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
- EIA/TIA-568 100Ω STP (maximum 100m)
- 100BASE-TX: UTP category 5, 5e cable (maximum 100m)
- EIA/TIA-568 100Ω STP (maximum 100m)
- 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum :)
- EIA/TIA-568 100Ω STP (maximum 100m)
- 1000BASE-X MMF, SMF

Cantidad de Ventiladores

2 Fans

Cerradura de Seguridad Física

Yes

Fuente de Alimentación

100–240V AC, 50/60 Hz

Puertos PoE+ (RJ45)

- Standard: 802.3at/802.3af compliant
- PoE Ports: Ports 1–16
- PoE Power Budget: 150 W

Dimensiones (W X D X H)

17.3 × 7.1 × 1.7 in (440 × 180 × 44 mm)

Consumo Máximo de energía

- 12.71 W (220/50Hz. no PD connected)
- 172.8 W (220/50Hz. with 150 W PD connected)

Disipación Máxima de Calor

- 43.34 BTU/h (no PD connected)
- 589.25 BTU/h (with 150 W PD connected)

RENDIMIENTO

Capacidad de Switcheo

7.2 Gbps

Tasa de Reenvío de Paquetes

5.36 Mpps

Tabla de MAC Address

8K

Jumbo Frame

10 KB

CARACTERÍSTICAS DE SOFTWARE

Características Avanzadas

- Compatible With IEEE 802.3at/af Compliant PDs
- Extend Mode (Up to 250m PoE power supply and data transm
- Priority Mode
- Isolation Mode
- Mac Address Auto-Learning And Auto-Aging
- IEEE802.3x Flow Control

Método de Transmisión

Store-And-Forward

OTROS

Certificación

CE, FCC, RoHS

Contenidos del Paquete

- TL-SL1218P
- Power Cable
- Installation Guide
- Two mounting brackets and the fittings
- Operating Temperature: 0–50 °C (32–122 °F)
- Storage Temperature: -40–70 °C (-40–158 °F)
- Operating Humidity: 10–90% RH non-condensing
- Storage Humidity: 5–90% RH non-condensing

Ambiente

100m)

ission)